

CUSTOM MADE GREEK-ITALIAN HYDROBLAST 500 BAR SYSTEM



- In stock in Athens
- Free of charge delivery to the warehouse you will select with company trucks
- Unit guarantee: 12 months
- Technical support in Greece and full set of spare parts for anything you may need

- Stainless steel 304L frame
- IP55 electric motor
- Motor efficiency class IE2
- Automatic star delta starter
- Direct drive pump
- Hardened brass crankshaft drive pump with triple ceramic plungers for high efficiency, long service life and low maintenance costs
- Pump oil level indicator
- Pump max. water temperature at 45°C
- Thermal valve
- Pressure regulator valve (adjusting pressure from 50 bar up to max. operating pressure)
- Safety valve (set 10% above operating pressure) for pump protection against overpressure
- Water strainer for long service life of the pump
- Inlet pressure switch against poor water flow
- High pressure gauge for accurate display readings
- Certification of 45' machine test run on max. operating pressure
- Max. operating pressure: 500 bar

- Voltage: 380-400 V
- Frequency: 50-60 Hz
- Max. water flow rate: 15 lpm @ 380V
- Max. water flow rate: 18 lpm @ 440V
- Motor output power: 15 kW/20 HP
- Plunger material: Ceramic
- Pump head material: Hardened brass
- Motor speed: 1450 rpm
- Crankshaft speed: 1450 rpm
- Weight: 170 kg
- Dimensions LxWxH: 95x78x75 cm

Includes:

High pressure gun
70cm high pressure lance

Flat jet nozzle
10 m High pressure hose 3/8"
Manual book

OPTIONAL EQUIPMENT



20 m HP hose 3/8" 500 bar with fittings & connecting nipple.



Rotating nozzle 600 bar designed to improve the cleaning efficiency of your high pressure washer by producing a rotating action that greatly expands the contact area of the cleaning stream, while providing the impact of a zero-degree nozzle



Sandblasting kit 500 bar consisting of:

- Sandblast head with flat jet
- High-strength carbide nozzle
- Stainless steel adjustable probe
- Spiral hose 5m ø19



- Personal protective equipment
- TST Apron 5/5/2 (one size)
- TST Head protection complete 20/30 (one size)
- Spirale Boots 800 bar (43-44-45)
- TST Gloves (pair) with inner glove 500 bar 5/5/2 (9, 11)



Important Notice!

Operation of the machine must be done by an officially certified user (wja) only. Special protective equipment for waterblasting (tst) must be worn at all times.

CUSTOM MADE GREEK-ITALIAN AIRLESS PAINT SPRAYING UNIT 30:1



- In stock in Piraeus
- Free of charge delivery to the warehouse you will select with company trucks
- Packaging: Standard, not seaworthy
- Unit guarantee: 12 months
- Technical support in Greece and full set of spare parts for anything you may need

Ideal for both large and small surface areas, this pump stands out for its durability and cost-effective design.

- Technically advanced, oil-free, low-icing and high-performance air motor
- Compact air regulator mounted directly on the motor

Stainless steel high-pressure filter and material pump for long-lasting performance

Materials:

- Primers
- Sprayable paints and varnishes
- Antirust paints
- Low-solvent and solvent-free paints
- Stains
- Water-based varnishes
- Transparent lacquers

Technical Characteristics

Model	AIRLESS 30:1
Maximum fluid working pressure:	214 bar
Maximum air input pressure page:	7 bar
Ratio:	30:1
Air inlet size:	¼" NPT (F)
Fluid inlet size:	¾" NPT
Displacement per cycle:	61cc
Fluid flow at 60 cycles per minute:	3.69 / Lt.
Maximum operating temperature:	82°C
Weight:	35 kg
Dimensions LxWxH:	65 x 55 x 130 cm



LAMMAR EQUIPMENT LP

196, Syngrou Ave, Kallithea, GR 17671
Tel: +30 697 877 8070

info@Lammar.gr
L.maragou@Lammar.gr
www.Lammar.gr